SODIMM DDR2 PC2-6400 800 MHz

Features

- Fully PC2-6400 Compliant (DDR2 800)
- Backward compatible with PC2-4300 (DDR2 533) PC2-5300 (DDR2 667)
- JEDEC-Standard 200-pin Small Outline Dual Inline Memory Module (SODIMM)
- Unbuffered
- Cas Latency 6
- Power Supply: 1.8V ± 0.2V
- 64ms, 8k refresh
- Serial Presence Detect (SPD)
- Pure Power and Ground Planes
- Gold PCB connector

Ordering Information

	DENSITY	REFERENCE	EAN
Optima	1GB	SODI101GBN/6400/2-BX	3536401460558
Optima	2GB	SODI102GBN/6400/2-BX	3536401460725
Premium	1GB	SODI101GBN/6400/2-SB	3536401462644
Premium	2GB	SODI102GBN/6400/2-SB	3536401462699
Premium	Kit 2GB (2x1GB)	K-SODI2GBN/6400/2-SB	3535401002680

Some of our capacities are also available in Premium packagings for distribution and integration purposes.

Optima packaging

Premium packaging

Product and specifications discussed here in are for evaluation and reference purpose only and are subject to change by PNY Technologies without notice.

Not sure of your memory needs ?

Try our online configurator !

PNY.EU

For more information, visit : WWW.PNY.EU

PNY Technologies Europe - RCS Bordeaux B394790430. PNY, PNY Technologies and the PNY logo are registered trademarks of PNY Technologies Inc. All other trademarks and logos are the property of their respective companies. Copyright ©2009 PNY Technologies, Inc. All rights reserved.